

1           1. A wireless terminal comprising:  
 2           an antenna;  
 3           a first visual indicator that indicates to a user of said wireless terminal when a radio is  
 4 transmitting; and  
 5           a signal lead for carrying an RF signal from said radio to said antenna and from said  
 6 antenna to said radio and for carrying a first baseband signal from said radio to said first visual  
 7 indicator for activating said first visual indicator.

1           2. The wireless terminal of claim 1 further comprising said radio.

1           3. The wireless terminal of claim 2 wherein said radio is integral to a PC radio card.

1           4. The wireless terminal of claim 1 wherein said signal lead is connected to said radio  
 2 by a detachable connector.

1           5. The wireless terminal of claim 1 further comprising a second visual indicator that  
 2 indicates when said radio is receiving and wherein said signal lead also carries a second  
 3 baseband signal from said radio to said second visual indicator.

1           6. A wireless terminal comprising:  
 2           an antenna;  
 3           a first visual indicator that indicates to a user of said wireless terminal when a radio is  
 4 receiving; and  
 5           a signal lead for carrying an RF signal from said radio to said antenna and from said  
 6 antenna to said radio and for carrying a first baseband signal from said radio to said first visual  
 7 indicator for activating said first visual indicator.

1           7. The wireless terminal of claim 6 further comprising said radio.

1           8. The wireless terminal of claim 7 wherein said radio is integral to a PC radio card.

1           9. The wireless terminal of claim 6 wherein said signal lead is connected to said radio  
 2 by a detachable connector.

08909001-080897

1           **10.** The wireless terminal of claim 6 further comprising a second visual indicator that  
 2 indicates when said radio is transmitting and wherein said signal lead also carries a second  
 3 baseband signal from said radio to said second visual indicator.

1           **11.** A wireless terminal comprising:  
 2 a radio;  
 3 an antenna;  
 4 a first visual indicator that indicates to a user of said wireless terminal when said radio is  
 5 operating; and  
 6 a cable that is detachably connected to said radio and that is also connected to said  
 7 antenna for carrying an RF signal and for carrying a baseband signal from said radio to said first  
 8 visual indicator.

1           **12.** The wireless terminal of claim 11 wherein said first visual indicator indicates when  
 2 said radio is receiving and further comprising a second visual indicator that indicates when said  
 3 radio is transmitting and wherein said cable also carries a second baseband signal from said radio  
 4 to said second visual indicator.

1           **13.** A radio card comprising:  
 2 a radio;  
 3 a detachable connector;  
 4 a first lead for carrying an RF signal from said radio to said detachable connector and  
 5 from said detachable connector to said radio and for carrying a first baseband signal indicative of  
 6 when said radio is operating.

1           **14.** The radio card of claim 13 wherein said first baseband signal is indicative of when  
 2 said radio is transmitting.

1           **15.** The radio card of claim 13 wherein said first baseband signal is indicative of when  
 2 said radio is receiving.

1           **16.** The radio card of claim 13 wherein said first lead also carries a second baseband  
 2 signal indicative of when said radio is transmitting.

- 3           17. The radio card of claim 13 wherein said first lead also carries a second baseband  
4   signal indicative of when said radio is receiving.

08909001.080897